

MOTOPOMPA DIESEL SELFPRIMING DIESEL ENGINE PUMP



Motopompa autoadescante monoblocco girante aperta con motore diesel. La valvola di ritegno incorporata nella bocca aspirante impedisce all'arresto l'effetto sifone e assicura il riadescamento automatico, ad ogni avviamento la pompa si riadesca anche se riempita solo parzialmente di liquido e con il tubo aspirante completamente vuoto. Impiegate nei drenaggi di acque pulite o leggermente sporche, nell'irrigazione a scorrimento e in interventi di svuotamento.

Selfpriming monoblock water pumps open impeller with diesel engine. The check valve inside the suction outlet avoids the syphon effect when stopping and assures the automatic re-start each time. The pump selfprimes even if partially filled and if the suction hose is completely empty. Suitable to drain clean or slightly dirty water and in flood irrigation systems. Recoil or electric starter with battery.

Aspirazione mandata / Suction delivery	80 (3")
Giri-min / r.p.m.	3200
Portata max. / Delivery max. (l/1')	900
Prevalenza max. / Head max. (m)	21
Altezza aspirazione / Suction depth (m)	7
Potenza motore Motor power (hp)	HAILIN diesel expert 6 (HL 178)
Capacità serbatoio / Tank Capacity (lt)	3,5
Avviamento / Start system	manuale - elettrico recoil - electric
Dimensioni / Dimensions (mm)	690 x 660 x 720

